

POLARIS®

OFF-ROAD VEHICLES

THE WORLD LEADER IN OFF-ROAD

STONQ



POLARIS
GENERAL

POLARIS
RANGER

POLARIS
RZR

POLARIS
SPORTSMAN

POLARIS
ACE

POLARIS®

OFF-ROAD VEHICLES

> BEST SELLING IN EVERY CATEGORY

For 34 years, Polaris® has built the world's best off-road vehicles. Engineered with class-leading performance, and infused with unmatched capabilities and unrivaled toughness. Nothing else comes close.



POLARIS
RANGER

P4



POLARIS
GENERAL

P8



POLARIS
RZR

P10



POLARIS
SPORTSMAN

P14

DRIVEN TO DO MORE™

> HARDEST WORKING. SMOOTHEST RIDING.®

While others aspire, RANGER® continues to define the utility side-by-side category with barrier-breaking innovation, class-leading performance, an unstoppable work ethic and a never quit mentality.

RANGER XP® 1000 EPS

> CONNECT AND TAKE COMMAND

POLARIS
RIDE COMMAND™

The RIDE COMMAND® factory-installed package is now available on select 3-seat RANGER XP® 1000 models, including the NorthStar Edition. Equipped with a 7" glove-touch display, front and rear cameras, in-dash speakers, built-in GPS navigation and Bluetooth® connectivity.

RIDE COMMAND® PACKAGE AVAILABLE ON SELECT RANGER MODELS

> COMFORT AT YOUR CONTROL

The NorthStar Edition is equipped with the premium RANGER Pro Shield™ cab system with 3-times better dust control over the competition. It features factory-installed heating and conditioning to keep you working comfortably in any climate.

NORTHSTAR EDITION AVAILABLE IN MULTIPLE COLORS

RANGER XP® 1000
NORTHSTAR® EDITION

CHOOSE YOUR RANGER®

2-SEAT MODEL

BEST-IN-CLASS UTILITY VALUE

- » 2-SEAT CAPACITY
- » UP TO 44 HP
- » 1,500 LB TOWING CAPACITY
- » 10 IN GROUND CLEARANCE

MODEL SHOWN: RANGER® 570 EPS



3-SEAT MODEL

MAXIMUM CAPABILITY

- » 3-SEAT CAPACITY
- » UP TO 82 HP
- » UP TO 2,500 LB TOWING CAPACITY
- » UP TO 13 IN GROUND CLEARANCE

MODEL SHOWN: RANGER XP® 1000 EPS



CREW MODEL

COMFORTABLE SEATING UP TO 6

- » UP TO 82 HP
- » UP TO 2,500 LB TOWING CAPACITY
- » UP TO 1,750 LB PAYLOAD CAPACITY
- » UP TO 13 IN GROUND CLEARANCE

MODEL SHOWN: RANGER CREW® XP 1000 EPS



SEE FULL SPECS ON PAGE 18



*Excluding High Lifter Editions. See your authorized Polaris dealer for details.

THE NEW STANDARD

FOR 6 PASSENGER UTILITY

› MORE RUGGED. MORE REFINED. MORE RANGER.™

82

HORSEPOWER

2,500LB

TOWING CAPACITY

13IN

GROUND CLEARANCE

RANGER CREW® XP 1000 EPS

› UNDISPUTED KING OF MUD



RANGER XP 1000 EPS HIGH LIFTER EDITION

› EXTREME MUD PERFORMANCE

- › **NEW!** REDESIGNED PREMIUM HALF DOORS WITH 1" WATER DRAINS
- › **NEW!** GEARED REVERSE TRANSMISSION
- › HIGH MOUNTED AIR INTAKES & VENT LINES
- › 82 HP WITH MUD SPECIFIC CAPABILITIES
- › 28" OUTLAW - 2 TIRES



RANGER CREW® XP 1000 EPS HIGH LIFTER EDITION

› INDUSTRY'S ONLY 6-SEAT MUD MACHINE

› BEST-IN-CLASS POWER



RANGER XP 900 EPS

› WORLD'S BEST-SELLING UTILITY SXs

BUILT FOR LIFE



POLARIS GENERAL® 1000 EPS RIDE COMMAND

ANY TASK. ANY TRAIL.

Any task or any trail, anything goes with Polaris GENERAL®. A day of chores or day of thrills, escape with Polaris GENERAL®. Packed with the ideal combination of power, capability, control, and comfort, it's the ultimate do-it-all, accept-no-excuses performance rec-utility vehicle. Whether you're in search of big adventure, hauling big loads, or tracking big game, Polaris GENERAL® is always ready.

UNSTOPPABLE POWER

100 HORSEPOWER | **600 LB** CARGO CAPACITY | **1,500 LB** TOWING CAPACITY

POLARIS GENERAL® 1000 EPS DELUXE



CHOOSE YOUR GENERAL®

BASE

- » 1000 PROSTAR® 100 HP ENGINE
- » STANDARD HALF-DOORS
- » ELECTRONIC POWER STEERING (EPS)
- » DUMPING BOX & TAILGATE
- » LOCK & RIDE® COMPATIBLE
- » VERSATRAC TURF MODE



MODEL SHOWN: POLARIS GENERAL® 1000 EPS

PREMIUM

- » AUTOMOTIVE PAINT
- » MATTE BLACK CAST ALUMINUM WHEELS
- » LOW-PROFILE FRONT BUMPER
- » POLARIS® HD 4,500 LB WINCH



MODEL SHOWN: POLARIS GENERAL® 1000 EPS PREMIUM

DELUXE

- » FOX® 2.0 PODIUM X QS3 SHOCKS
- » POLARIS® LOCK & RIDE® SPORT ROOF
- » MTX® PREMIUM SOUNDBAR
- » CONVEX REARVIEW MIRROR



MODEL SHOWN: POLARIS GENERAL® 1000 EPS DELUXE

MULTI-PASSENGER

- » LOW-PROFILE FRONT BUMPER
- » POLARIS® HD 4,500 LB WINCH
- » NEW FOX® 2.0 PODIUM X QS3 SHOCKS
- » 27" GBC® DIRT COMMANDER 8-PLY TIRES



MODEL SHOWN: POLARIS GENERAL® 4 1000 EPS

UNCOMPROMISING CAPABILITIES

12 IN GROUND CLEARANCE | **13.3 IN** SUSPENSION | **0-40 MPH** CLASS-LEADING ACCELERATION

POLARIS GENERAL® 4 1000 EPS



SEE FULL SPECS ON PAGE 24

LIVE WIDE OPEN



RZR XP® TURBO S

RZR® TURBO S

> FEAR THE BEAST

168
HORSEPOWER

72IN
WHEELBASE

25IN
SUSPENSION



RZR XP® 1000

> NASTY OUTSIDE

Cut more aggressively with menacing looks and wicked LED accents, all hint at the heart of the animal within.



RZR XP® TURBO S

> NICE INSIDE

A new driving position with race-inspired ergonomics, and a redesigned interior with premium digital displays for navigating rugged terrain at speed.

INTRODUCING THE NEW
RZR XP® 1000 LINE-UP

RZR XP® 1000
DYNAMIX

Grab a DYNAMIX™ Edition and discover the terrain dominating savagery of active suspension.



POLARIS®
RZR®
RS1

> MOST AGILE RZR® EVER

110 HORSEPOWER | **83IN** OPTIMAL WHEELBASE | **21IN** SUSPENSION



RZR XP® 1000

> **RZR XP® 1000**

Ideally balanced extreme performance - instant response of 110-horsepower and 64-inch stance stability.

POLARIS®
RIDECOMMAND®



RZR XP® 1000 RIDE COMMAND®

> **RZR XP® 1000 RIDE COMMAND®**

Upgrade with a Ride Command® Edition, including off-road worthy 7" touchscreen that puts total control at your fingertips plus premium styling & LED lighting

ALL-NEW

RZR XP® TURBO S
168 HP



ALL-NEW

RZR® RS1
110 HP



TRAIL 50 IN WIDE

RZR® 570
45 HP



RZR® 900
75 HP



EXTREME PERFORMANCE 64 IN WIDE

RZR XP® 1000
110 HP



AVAILABLE
4 SEAT

RZR XP® 1000 DYNAMIX
110 HP



AVAILABLE
4 SEAT

RZR XP® TURBO
168 HP



AVAILABLE
4 SEAT

SPORT 60 IN WIDE

RZR® S 900
75 HP



RZR® S 1000
110 HP



AVAILABLE
4 SEAT

LEGENDARY TOUGH



SPORTSMAN® 570 SP

> ENGINEERED TO ENDURE

For more than 30-years, Sportsman® has defined a category through industry-leading innovations and a renowned level of toughness. The rider-inspired design of Sportsman® delivers all-day comfort, class-leading storage, unmatched convenience, and hard-nosed performance that never quits.

> RIDE HARDER

Up to 11.5 IN of Ground Clearance



SPORTSMAN® 570 SP

CHOOSE YOUR SPORTSMAN®

SPORTSMAN® 450 H.O.

- » UP TO 33 HP
- » 1,225 LB TOWING CAPACITY
- » 10.5 IN GROUND CLEARANCE



SPORTSMAN® 450 UTILITY EDITION

- » HEAVY DUTY 6-PLY TIRES
- » FRONT & REAR STEEL RACKS
- » FRONT & REAR RECEIVER HITCH



SPORTSMAN® 570

- » UP TO 44 HP
- » 1,225 LB TOWING CAPACITY
- » 11 IN GROUND CLEARANCE



> GO FURTHER

Industry-Leading 8 Gallons of Sealed Storage



SPORTSMAN® 570 EPS UTILITY EDITION

- » HEAVY DUTY 6-PLY TIRES
- » FRONT & REAR STEEL RACKS
- » FRONT & REAR RECEIVER HITCH



SPORTSMAN® 570 SP

- » UP TO 44 HP
- » 1,500 LB TOWING CAPACITY
- » 11.5 IN GROUND CLEARANCE



SPORTSMAN® 570 SP HUNTER EDITION

- » POLARIS PURSUIT CAMO® GRAPHICS
- » 2,500 LB POLARIS HD WINCH
- » GUN SCABBARD & BUMPERS



> DO MORE

Up to 1,500 lbs of Towing Capacity



SPORTSMAN® 570 SP

SPORTSMAN® X2 570 EPS

- » 1,500 LB TOWING CAPACITY
- » 11.5 IN GROUND CLEARANCE
- » CARGO BOX WITH FLIP-UP SEAT



SPORTSMAN® TOURING 570

- » UP TO 44 HP
- » 1,225 LB TOWING CAPACITY
- » INTEGRATED PASSENGER SEAT



SPORTSMAN® TOURING 570 SP

- » ELECTRIC POWER STEERING (EPS)
- » 1,500 LB TOWING CAPACITY
- » INTEGRATED PASSENGER SEAT



SEE FULL SPECS ON PAGE 22

RIDES



SINGLE SEAT FREEDOM

POLARIS ACE 900 XC

A black and red Polaris RZR XP 1000 XC side-by-side utility vehicle. The vehicle features a roll-over protection structure (ROPS), large off-road tires, and a prominent front grille with the Polaris logo. The text "1000 XC" is visible on the side of the vehicle.

		2-SEAT		3-SEAT			CREW				
											
		RANGER® 500	RANGER® 570 EPS <i>AVAIL. BASE</i>	RANGER® 570 FULL-SIZE	RANGER XP® 900 EPS, EPS PAINTED <i>AVAIL. BASE</i>	RANGER XP® 1000 EPS <i>AVAIL. BASE</i>	RANGER CREW® 570-4 EPS <i>AVAIL. BASE</i>		RANGER CREW® 570 FULL-SIZE	RANGER CREW® XP 900 EPS <i>AVAIL. BASE</i>	RANGER CREW® XP 1000 EPS <i>AVAIL. BASE</i>
ENGINE / DRIVE TRAIN	Engine Type	4-Stroke Single-Cylinder	4-Stroke Single-Cylinder DOHC	4-Stroke Single-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Single-Cylinder DOHC		4-Stroke Single-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC
	Horsepower	32 HP	44 HP	44 HP	68 HP	82 HP	44 HP		44 HP	68 HP	82 HP
	Drive System	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	High-Performance On-Demand True AWD / 2WD/ VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode		On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	High Performance On-Demand True AWD / 2WD / VersaTrac Turf Mode
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard	Not Equipped		Not Equipped	Not Equipped	Standard
SUSPENSION	Front Suspension	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10" (25.4 cm) Travel	Dual A-Arm 11" (27.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel		MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10" (25.4 cm) Travel	Dual A-Arm 11" (27.9 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 11" (27.9 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel		Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 11" (27.9 cm) Travel
TIRES AND WHEELS	Front Tires	25 x 8-12; 489	25 x 8-12; 489	25 x 8-12; 489	26 x 9-12; PXT <i>25 x 10-12; 489</i>	27 x 9-12; Maxxis® MU51 <i>26 x 9-12; PXT</i>	25 x 10-12; 489		25 x 10-12; 489	26 x 9-12; PXT	27 x 9-12; Maxxis® MU11 <i>26 x 9-12; PXT</i>
	Rear Tires	25 x 10-12; 489	25 x 10-12; 489	25 x 10-12; 489	26 x 11-12; PXT <i>25 x 11-12; 489</i>	27 x 11-12; Maxxis® MU521 <i>26 x 11-12; PXT</i>	25 x 10-12; 489		25 x 10-12; 489	26 x 11-12; PXT	27 x 11-12; Maxxis® MU21 <i>26 x 11-12; PXT</i>
	Wheels	Stamped Steel	Aluminum Black Xcelerator <i>Stamped Steel</i>	Stamped Steel	Aluminum Black Xcelerator <i>Stamped Steel</i>	Aluminum Black Xcelerator 2.0 <i>Stamped Steel</i>	Aluminum Black Xcelerator <i>Stamped Steel</i>		Stamped Steel	Aluminum Black Xcelerator <i>Stamped Steel</i>	Aluminum Black Xcelerator 2.0 <i>Stamped Steel</i>
DIMENSIONS / CAPACITIES	Wheelbase	73" (185.4 cm)	73" (185.4 cm)	79" (202 cm)	81" (206 cm)	81" (206 cm)	105" (266.7 cm)		107" (272.6 cm)	113" (287 cm)	113" (287 cm)
	Dry Weight	1,065.9 lb (483 kg)	1,101.9 lb (501 kg) <i>1,073 lb (488 kg)</i>	1,070.6 lb (486 kg)	1,342 lb (610 kg) <i>1,324.4 lb (601 kg)</i>	1,565 lb (709.9 kg) <i>1,546 lb (701.3 kg)</i>	1,351.2 lb (614 kg) <i>1,326.2 lb (603 kg)</i>		1,392.5 lb (632 kg)	1,629 lb (738.9 kg) <i>1,612 lb (733 kg)</i>	1,829 lbs (830kg) <i>1,810 lbs (821 kg)</i>
	Overall Vehicle Size (L x W x H)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	114 x 60 x 74" (290 x 152 x 188 cm)	116.5 x 60 x 76" (296 x 152 x 193 cm)	120 x 62.5 x 77" (305 x 158 x 196 cm)	142 x 60 x 73" (361 x 152 x 185 cm)		146 x 60 x 74" (370 x 152 x 188 cm)	148.5 x 61 x 76" (377 x 155 x 193 cm)	152 x 62.5 x 77" (386 x 158 x 196 cm)
	Ground Clearance	10" (25.4 cm)	10" (25.4 cm)	10.5" (26.7 cm)	12" (30.5 cm) <i>11.5" (29.2 cm)</i>	13" (33 cm) <i>12.5" (31.8 cm)</i>	10" (25.4 cm)		10.5" (26.7 cm)	11.3" (28.7 cm)	13" (33 cm) <i>12.5" (31.8 cm)</i>
	Seating Capacity	2	2	3	3	3	4		6	6	6
	Fuel Capacity	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	10 gal (37.9 L)	11.5 gal (43.5 L)	9 gal (34.1 L)		9 gal (34.1 L)	10 gal (37.9 L)	11.5 gal (37.9 L)
	Bed Box Dimensions (L x W x H)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.75 x 54.2 x 12.5" (93.3 x 137.8 x 31.8 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)		36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.75 x 54.2 x 12.5" (93.3 x 137.8 x 31.8 cm)
	Box Capacity	500 lb (226.8 kg)	500 lb (226.8 kg)	800 lb (363 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	500 lb (226.8 kg)		800 lb (363 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)
	Payload Capacity	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,250 lb (567 kg)		1,500 lb (680.4 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	2,000 lb (907.2 kg)	2,500 lb (1,133.9 kg)	1,500 lb (680.4 kg)		1,500 lb (680.4 kg)	2,000 lb (907.2 kg)	2,500 lb (1,133.9 kg)
FEATURES	Electronic Power Steering	Not Equipped	Standard / <i>Accessory Option</i>	Not Equipped	Standard / <i>Accessory Option</i>	Standard	Standard / <i>Accessory Option</i>		Not Equipped	Standard / <i>Accessory Option</i>	Standard
	Adjustable Driver's Seat	Not Equipped	Not Equipped	Not Equipped	Standard <i>Not Equipped</i>	Standard <i>Not Equipped</i>	Not Equipped		Not Equipped	Standard on Silver Pearl <i>Not Equipped</i>	Standard <i>Not Equipped</i>
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard		Standard	Standard	Standard
Color		Sage Green, Solar Red	Nara Bronze <i>Sage Green, Polaris® Pursuit® Camo</i>	Solar Red, Sage Green	Solar Red, Sage Green, Military Tan, Orange Madness, Silver Pearl <i>Sage Green, Polaris® Pursuit® Camo</i>	Steel Blue, Magnetic Gray, Pearl White, Polaris® Pursuit® Camo <i>Sage Green</i>	Nara Bronze <i>Sage Green, Polaris® Pursuit® Camo</i>		Sage Green	Polaris® Pursuit® Camo, Silver Pearl <i>Sage Green</i>	Sunset Red, Polaris® Pursuit® Camo, Pearl White <i>Sage Green</i>

SPECIAL EDITIONS

NORTHSTAR EDITION
RANGER XP® 1000 FEATURES PLUS:

- » Premium RANGER Pro Shield™ Cab
- » Fixed-Glass Windshield with Wiper
- » Rear Glass Panel
- » Dome Light, Rear View Mirror
- » Heat, AC, Defrost



NORTHSTAR CREW EDITION
RANGER CREW® XP 1000 FEATURES PLUS:

- » Premium RANGER Pro Shield™ Cab
- » Fixed-Glass Windshield with Wiper
- » Rear Glass Panel
- » Dome Light, Rear View Mirror
- » Heat, AC, Defrost



HIGH LIFTER EDITION
RANGER XP® 1000 FEATURES PLUS:

- » Mud-Specific Gearing
- » High-Mount Air Intake and Vent Lines
- » 13.5" Ground Clearance
- » 28" Outlaw 2 Tires
- » Polaris® Pro 4,500 LB HD Winch



HIGH LIFTER CREW EDITION
RANGER CREW® XP 1000 FEATURES PLUS:

- » Mud-Specific Gearing
- » High-Mount Air Intake and Vent Lines
- » 13.5" Ground Clearance
- » 28" Outlaw 2 Tires
- » Polaris® Pro 4,500 LB HD Winch



		TRAIL		SPORT		XTREME				MULTI			
													
ENGINE / DRIVE TRAIN	Engine Type	ProStar® 570; 4-Stroke DOHC Single-Cylinder	ProStar® 900; 4-Stroke DOHC Twin-Cylinder	ProStar® 900; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000 H.O.; 4-Stroke DOHC Twin Cylinder	ProStar® 1000 H.O.; 4-Stroke DOHC Twin-Cylinder	ProStar® Turbo H.O.; 4-Stroke DOHC Twin-Cylinder Turbocharged	ProStar Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000 H.O.; 4-Stroke DOHC Twin-Cylinder	ProStar 1000 H.O.; 4-Stroke DOHC Twin Cylinder	ProStar® Turbo H.O.; 4-Stroke DOHC Twin-Cylinder Turbocharged"
	Horsepower	45 HP	75 HP	75 HP	100 HP	110 HP	110 HP	168 HP	168 HP	100 HP	110 HP	110 HP	168 HP
	Drive System	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD / VersaTrac Turf Mode</i>	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD</i>	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD</i>	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	Isolated Xtreme Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD
	Engine Braking System	Not Equipped <i>Standard</i>	Standard	Standard	Standard	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 9" (22.9 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Wheel Travel	Dual A-Arm with 12.25" (31.1 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 12.25" (31.1 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 25" (63.5 cm) Travel	Dual A-Arm with Stabilizer Bar 12.25" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel
	Front Shocks	ZF Sachs®	ZF Sachs®	FOX® 2.0 PERFORMANCE PODIUM <i>2" Walker Evans® Needle</i>	2" Walker Evans® Needle	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	FOX® 2.5 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX® 2.0 PODIUM X	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers
	Rear Suspension	Dual A-Arm with Stabilizer Bar and 9.5" (24 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 25" (63.5 cm) Travel	Dual A-Arm with Stabilizer Bar 13.2" (33.5 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel
	Rear Shocks	ZF Sachs®	ZF Sachs®	FOX® 2.0 PERFORMANCE PODIUM <i>2" Walker Evans® Needle</i>	2" Walker Evans® Needle	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	FOX® 3.0 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX® 2.0 PODIUM X	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers
TIRES AND WHEELS	Front Tires	25 x 8-12; Ancla® <i>25 x 8-12; Maxxis®</i>	26 x 8-12; PXT	27 x 9-12; GBC® Dirt Commander	27 x 9-12; GBC® Dirt Commander	29 x 9-14 Maxxis Bighorn	29 x 9-14; Maxxis® Bighorn	29 x 9-14 Maxxis® Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	27 x 9-12; GBC® Dirt Commander	29 x 9-14; Maxxis® Bighorn	29 x 9-14; Maxxis® Bighorn	29 x 9-14 Maxxis® Bighorn
	Rear Tires	25 x 10-12; Ancla® <i>25 x 10-12; Maxxis®</i>	26 x 9-12; PXT	27 x 11-12; GBC® Dirt Commander	27 x 11-12; GBC® Dirt Commander	29 x 11-14 Maxxis Bighorn	29 x 11-14; Maxxis® Bighorn	29 x 11-14 Maxxis® Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	27 x 11-12; GBC® Dirt Commander	29 x 11-14; Maxxis® Bighorn	29 x 11-14; Maxxis® Bighorn	29 x 11-14 Maxxis® Bighorn
	Wheels	Stamped Steel <i>Cast Aluminum</i>	Stamped Steel <i>Cast Aluminum</i>	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	15" Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS / CAPACITIES	Wheelbase	77" (196 cm)	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)	83"	90" (228.6 cm)	90" (228.6 cm)	90"	106.5" (270.5 cm)	117" (297.2 cm)	117" (297.2 cm)	117" (297.2 cm)
	Dry Weight	996 lb (452 kg) <i>1,077 lb (489 kg)</i>	1,150 lb (522 kg) <i>1,176 lb (533 kg)</i>	1,204 lb (546 kg) <i>1,230 lb (558 kg)</i>	1,255 lb (560 kg)	1340 lbs (607.8kg)	1,369 lb (621 kg)	1,487 lbs (676 kg)	1,718 lbs (779.3 kg)	1,476 lb (670 kg)	1,659 lbs (754 kg)	1,586 lbs (719 kg)	1,698 lbs (772kg)
	Overall Vehicle Size (L x W x H)	107.5 x 50 x 69" (273 x 127 x 175.2 cm)	108 x 50 x 69.5" (274.3 x 127 x 176.5 cm)	106 x 60 x 71.5" (269.2 x 152.4 x 181.6 cm)	108 x 60 x 71.5" (274.3 x 152.4 x 181.6 cm)	112" x 64" x 73.7" (284.5 x 162.6 x 187.3 cm)	119 x 64 x 73.7" (302.2 x 162.6 x 187.3 cm)	119 x 64 x 73.7" (302.2 x 162.6 x 187.3 cm)	122" x 74.5" x 8" (309.9 x 190.5 x 203.2 cm)	138.1 x 60 x 71.7" (350.8 x 152.4 x 182.1 cm)	146 x 64 x 73.7" (370.8 x 162.6 x 187.3 cm)	146 x 64 x 73.8" (370.8 x 162.6 x 187.3 cm)	146 x 64 x 73.8" (370.8 x 162.6 x 187.3 cm)
	Ground Clearance	10.5" (26.7 cm)	11" (27.9 cm)	12.5" (31.8 cm)	12.5" (31.8 cm)	13"	13.5" (34.3 cm)	13.5" (34.3 cm)	16" (40.6 cm)	12.5" (31.8 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)
	Fuel Capacity	7.25 gal (27.4 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
	Bed Box Dimensions (L x W x H)	20 x 40 x 9" (51 x 102 x 23 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.5" x 23" x 4.1" (52 x 58 x 10.4 x 3 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
	Rear Rack Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	50 lb	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	300 lb (136.1kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
	Lighting	Halogen, 50W <i>Halogen, 55W low / 60W high</i>	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights

SPECIAL EDITIONS



RZR XP® 1000 DYNAMIX
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Dynamix™ Active Suspension
- » Dynamix™ Visualizer
- » Ride Command™ 7" Glove-Touch Display
- » Rear-Facing Camera
- » 900 Watt Stator
- » Available in a 4-Seat



RZR XP® 1000 RIDE COMMAND
SAME FEATURES AS RZR XP® 1000 PLUS:

- » 7" Glove-Touch Display
- » AM/FM Antenna
- » In-door Audio
- » Front and Rear Wired Cameras

 **DOWNLOAD THE FREE RIDE COMMAND® APP**



RZR XP® 4 1000 RIDE COMMAND
SAME FEATURES AS RZR XP® 4 1000 PLUS:

- » 7" Glove-Touch Display
- » AM/FM Antenna
- » In-door Audio
- » Front and Rear Wired Cameras

 **DOWNLOAD THE FREE RIDE COMMAND® APP**



RZR XP® 1000 HIGH LIFTER
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Front Bull Bumper with Winch Hook
- » Polaris® 4,500 lb Integrated Winch
- » High-Clearance Lower Control Arms
- » High-Clearance Lower Radius Rods
- » Outlaw™ 2 Tires
- » High-Mount Rear Intake System
- » Rearview Mirror and Half Doors
- » Available in a 4-Seat



RZR XP® 1000 TRAILS & ROCKS
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Front Bull Bumper with Tow Loop
- » Polaris® 4,500 lb Integrated Winch
- » High-Clearance Lower Control Arms
- » High-Clearance Lower Radius Rods
- » ProArmor™ Crawler X6 Tires with Beadlock Wheel
- » Rock Sliders and HMW Skid Plate
- » Rearview Mirror
- » High-Visibility Front Fender
- » Flares and Click-6 Harnesses

REC / UTILITY							SPORT / UTILITY					2-UP / UTILITY					MUD & SPORT			
																				
		SPORTSMAN® 450 H.O. AVAILABLE EPS	SPORTSMAN® 450 H.O. UTILITY EDITION	SPORTSMAN® 570 AVAILABLE EPS	SPORTSMAN® 570 EPS UTILITY EDITION	SPORTSMAN® 570 SP	SPORTSMAN® 570 SP HUNTER EDITION	SPORTSMAN® 850	SPORTSMAN® 850 SP		SPORTSMAN XP® 1000	SPORTSMAN XP® 1000 HUNTER EDITION	SPORTSMAN® X2 570 EPS	SPORTSMAN® TOURING 570 AVAILABLE EPS	SPORTSMAN® TOURING 570 SP	SPORTSMAN® TOURING 850 SP	SPORTSMAN TOURING XP® 1000	SPORTSMAN XP® 1000 HIGH LIFTER EDITION	SPORTSMAN® 850 HIGH LIFTER EDITION	
ENGINE / DRIVE TRAIN	Engine Type	ProStar® 500cc, 4-Stroke SOHC Single-Cylinder	ProStar® 500cc, 4-Stroke SOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 850cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 850cc, 4-Stroke SOHC Twin-Cylinder		ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 850cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 952cc, 4-Stroke SOHC Single-Cylinder	ProStar® 850cc, 4-Stroke SOHC Twin-Cylinder	
	Horsepower	33 HP	33 HP	44 HP	44 HP	44 HP	44 HP	78 HP	78 HP		90 HP	90 HP	44 HP	44 HP	44 HP	78 HP	88 HP	85 HP	78 HP	
	Drive System	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD		High Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD
	Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Standard / Not Equipped	Standard / Standard	Standard / Standard	Standard / Not Equipped	Standard / Standard		Standard / Standard	Standard / Standard	Standard / Standard	Not Equipped / Not Equipped	Standard / Standard	Standard / Standard	Standard / Standard	Standard / Standard	Not Equipped / Not Equipped	Not Equipped / Not Equipped
SUSPENSION	Front Suspension	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	High-Clearance Arched Dual A-Arm, 9" (22.9 cm) Travel	High-Clearance Arched Dual A-Arm, 9" (22.9 cm) Travel		High-Clearance Arched Dual A-Arm, 9" (22.9 cm) Travel	High-Clearance Arched Dual A-Arm, 9" (22.9 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	Dual A-Arm, 9" (22.9 cm) Travel	Dual A-Arm, 9" (22.9 cm) Travel	High-Clearance Arched Dual A-Arm, 7.4" (18.8 cm) Travel	High-Clearance Arched Dual A-Arm, 7.4" (18.8 cm) Travel	
	Rear Suspension	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel		High-Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, Rolled IRS, 10.2" (26 cm) Travel	Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 6.7" (17 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 6.7" (17 cm) Travel	
TIRES & WHEELS	Front Tires	24 x 8-12; NS388	24 x 8-12; NS388	25 x 8-12; 489	25 x 8-12; 489	26 x 8-14; CST / PXT 6-Ply Radial	26 x 8-14; CST / PXT 6-Ply Radial	26 x 8-14; CST	26 x 8-14; CST		26 x 8-14; CST	26 x 8-14; CST	25 x 8-12; 489	25 x 8-12; 489	26 x 8-14; CST	26 x 8-14; CST	26 x 9-14; PXT	29.5 x 9.5-14; Outlaw®	29.5 x 9.5-14; Outlaw®	
	Rear Tires	24 x 10-12; NS388	24 x 10-12; NS388	25 x 10-12; 489	25 x 10-12; 489	26 x 8-14; CST / PXT 6-Ply Radial	26 x 10-14; CST / PXT 6-Ply Radial	26 x 10-14; CST	26 x 10-14; CST		26 x 10-14; CST	26 x 10-14; CST	25 x 10-12; 489	25 x 10-12; 489	26 x 10-14; CST	26 x 10-14; CST	26 x 11-14; PXT	29.5 x 9.5-14; Outlaw®	29.5 x 9.5-14; Outlaw®	
	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Cast Aluminum	Cast Aluminum	Stamped Steel	Cast Aluminum		Cast Aluminum	Cast Aluminum	Stamped Steel	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Stamped Steel
DIMENSIONS / CAPACITIES	Wheelbase	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	53" (134.6 cm)	53" (134.6 cm)		53" (134.6 cm)	53" (134.6 cm)	56" (142.2 cm)	56" (142.2 cm)	56" (142.2 cm)	57" (144.8 cm)	57" (144.8 cm)	53" (134.6 cm)	53" (134.6 cm)	
	Dry Weight	701 lb (318 kg) 713 lb (323 kg)	721 lb (328 kg)	704 lb (330 kg) 716 lb (325 kg)	755 lb (343 kg)	730 lb (332 kg)	753 lb (342 kg)	771 lb (351 kg)	785 lb (359 kg)		805 lb (366 kg)	805 lb (366 kg)	788 lb (358 kg)	728 lb (330 kg) 739 lb (336 kg)	773 lb (351 kg)	804 lb (365 kg)	886 lb (403 kg)	974 lb (441 kg)	921 lb (417 kg)	
	Overall Vehicle Size (L x W x H)	83 x 48 x 47" (210.8 x 121.9 x 119.4 cm)	84 x 48 x 47" (213 x 121.9 x 119.4 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83.25 x 47.6 x 50.7" (211.4 x 120.9 x 128.9 cm)	83.25 x 47.6 x 50.7" (211.4 x 120.9 x 128.9 cm)		83.25 x 47.6 x 50.7" (211.4 x 120.9 x 128.9 cm)	83.25 x 47.6 x 50.7" (211.4 x 120.9 x 128.9 cm)	89 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86.5 x 47.6 x 58.2" (219.7 x 120.9 x 147.9 cm)	86.5 x 47.6 x 58.2" (219.7 x 120.9 x 147.9 cm)	83.25 x 47.6 x 50.7" (211.4 x 120.9 x 128.9 cm)	83 x 49 x 52" (210 x 124 x 132 cm)	
	Ground Clearance	10.5" (26.6 cm)	10.5" (26.6 cm)	11" (27.9 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)		11.5" (29.2 cm)	11.5" (29.2 cm)	11" (27.9 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11.2" (28.5 cm)	11.2" (28.5 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	
	Seat Height	33.25" (84.5 cm)	33.25" (84.5 cm)	33.75" (85.7 cm)	33.7" (85.7 cm)	34.2" (87 cm)	34.3" (87 cm)	37" (94 cm)	37" (94 cm)		37" (94 cm)	37" (94 cm)	33.7" (85.7 cm)	33.7" (85.7 cm)	34.2" (87 cm)	35.7" (90.8 cm)	35.7" (90.8 cm)	39" (99 cm)	39" (99 cm)	
	Fuel Capacity	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)		5.2 gal (19.9 L)	5.2 gal (19.9 L)	6.7 gal (26.3 L)	6.75 gal (26.3 L)	6.7 gal (26.3 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	
	Rear Box Dimensions (L x W x H)	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.		N.A.	N.A.	37.5 x 19.5 x 6.5" (95 x 49.5 x 16.5 cm)	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	
	Front/Rear Rack Capacity	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)		120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	90 lb (40.8 kg) / 400 lb (180 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	N.A. / 75 lb (34 kg)	
	Payload Capacity	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	575 lb (261 kg)	575 lb (261 kg)		575 lb (261 kg)	575 lb (261 kg)	705 lb (320 kg)	575 lb (261 kg)	485 lb (220 kg)	575 lb (261 kg)	575 lb (261 kg)	290 lb (132 kg)	290 lb (132 kg)	
Hitch Towing Rating	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,500 lb (680 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)		1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	
Colors		Sage Green, Indy Red <i>Indy Red, Orange Burst</i>	Ghost Gray	Sage Green, Velocity Blue, Polaris Pursuit® Camo <i>Sage Green, Velocity Blue, Polaris Pursuit® Camo</i>	Ghost Gray	Crimson Metallic, Magnetic Gray Metallic	Polaris Pursuit® Camo	Sage Green, Titanium Metallic	Matte Sunset Red, Titanium Matte Metallic, Polaris Pursuit® Camo		Havasu Red Pearl	Polaris Pursuit® Camo	Sage Green	Indy Red, <i>Velocity Blue</i>	Turbo Silver	Radar Blue	Crimson Metallic	Stealth Black	Cruiser Black	

2-SEAT				4-SEAT		SPECIAL EDITIONS			
									
		<i>POLARIS GENERAL® 1000</i>	<i>POLARIS GENERAL® 1000 PREMIUM</i>	<i>POLARIS GENERAL® 1000 DELUXE</i>	<i>POLARIS GENERAL® 4 1000</i>	<i>POLARIS GENERAL® 4 1000 RIDE COMMAND®</i>	<i>POLARIS GENERAL® 1000 RIDE COMMAND®</i>	<i>POLARIS GENERAL® 1000 HUNTER EDITION</i>	<i>POLARIS GENERAL® 1000 LIMITED EDITION</i>
ENGINE / DRIVE TRAIN	Engine Type	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder
	Horsepower	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP
	Drive System	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode
	Engine Braking System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel
	Front Shocks	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube
	Rear Suspension	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel
	Rear Shocks	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube
TIRES & WHEELS	Front Tires	27 x 9-12 NHS; CST Clincher	27 x 9-14; Maxxis® Coronado	27 x 9-14; Maxxis® Coronado	27 x 9-14; Dirt Commander	27 x 9-14; Dirt Commander	27 x 9-14; Maxxis® Coronado	27 x 9-14; Maxxis® Coronado	27 x 9-14; Maxxis® Coronado
	Rear Tires	27 x 11-12 NHS; CST Clincher	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado	27 x 11-14; Dirt Commander	27 x 11-14; Dirt Commander	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado
	Wheels	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS / CAPACITIES	Wheelbase	81" (206 cm)	81" (206 cm)	81" (206 cm)	113" (287 cm)	113" (287 cm)	81" (206 cm)	81" (206 cm)	81" (206 cm)
	Dry Weight	1,430 lb (648 kg)	1,491 lb (676 kg)	1,544 lb (700 kg)	1,857 lb (842 kg)	1,860 lb (842 kg)	1,544 lb (700 kg)	1,491 lb (676 kg)	1,491 lb (676 kg)
	Overall Vehicle Size (L x W x H)	116.4 x 62.5 x 73.8" (295.6 x 158.7 x 187 cm)	116.4 x 62.5 x 73.8" (295.6 x 158.7 x 187 cm)	118.2 x 62.5 x 75" (300 x 158.7 x 190.5 cm)	150.2 x 62.5 x 75" (381.5 x 158.7 x 190.5 cm)	150.2 x 62.5 x 75" (381.5 x 158.7 x 190.5 cm)	118.2 x 62.5 x 75" (300 x 158.7 x 190.5 cm)	118.2 x 62.5 x 73.8" (300 x 158.7 x 187 cm)	118.2 x 62.5 x 73.8" (300 x 158.7 x 187 cm)
	Ground Clearance	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)
	Fuel Capacity	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)
	Bed Box Dimensions (L x W x H)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)
	Rear Rack Capacity	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)
	Payload Capacity	1,100 lb (499 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)	1,280 lb (580 kg)	1,280 lb (580 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)
	Electronic Power Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Other Features			Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker, Bluetooth® AM/FM Soundbar, Convex Rear View Mirror	Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker Bluetooth® AM/FM Soundbar, Convex Rear View Mirror, Front & Rear On-board Cameras	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker Bluetooth® AM/FM Soundbar, Convex Rear View Mirror, Front & Rear On-board Cameras	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, Lock & Ride® Dual Gun Scabbard, Polaris® Gun Boots (Qty 2)	Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper Lock & Ride® Tip Down Headache Rack
Colors		White Lighting	Havasu Red	Orange Rust, Titanium Metallic	Matte White Metallic	Black Pearl	Black Pearl	Polaris Pursuit® Camo	Cruiser Black Breakout Camo

ENGINE								
		<i>OUTLAW® 50</i>	<i>OUTLAW® 110 EFI</i>	<i>SPORTSMAN® 110 EFI</i>	<i>POLARIS ACE® 150 EFI</i>	<i>RZR® 170 EFI</i>	<i>PHOENIX 200</i>	<i>RANGER® 150 EFI</i>
	Age	6+	10+	10+	10+	10+	14+	14+
	Engine Type	49cc, 4-Stroke Single-Cylinder	112cc, 4-Stroke Single-Cylinder	112cc, 4-Stroke Single-Cylinder	149cc, 4-Stroke Single-Cylinder	169cc, 4-Stroke Single-Cylinder	196cc, 4-Stroke Single-Cylinder	196cc, 4-Stroke Single-Cylinder
DRIVE TRAIN / SUSPENSION	Fuel System	Carbureted	EFI	EFI	EFI	EFI	Carbureted	Carbureted
	Cooling	Air	Air	Air	Air/Oil	Fan	Air	Air
	Transmission/Final Drive	Automatic PVT Forward; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; O-ring Chain	Automatic PVT F/N/R; Shaft	Automatic PVT F/N/R; Shaft
	Drive System	2WD	2WD	2WD	2WD	2WD	2WD	2WD
TIRES & WHEELS	Front Suspension	Single A-Arm with 3" (7.6 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Dual A-Arm 5.1" (13 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Dual A-Arm with 7" (17.8 cm) Travel	Dual A-Arm with 7" (17.8 cm) Travel
	Rear Suspension	Mono-Shock Swingarm with 3" (7.6 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Swingarm Dual Shocks with 6" (15.2 cm) Travel	Swingarm Dual Shocks with 5" (12.7 cm) Travel	Mono-Shock Swingarm with 6.5" (16.5 cm) Travel	Mono-Shock Swingarm with 6.5" (16.5 cm) Travel
	Front Tires	16 x 6.5-7	19 x 7-8	19 x 7-8	22 x 7-10	19 x 7-8	21 x 7-10	21 x 7-10
	Rear Tires	16 x 8-7	18 x 9.5-8	18 x 9.5-8	22 x 10-10	20 x 10-9	20 x 10-9	20 x 10-9
DIMENSIONS / CAPACITIES	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel
	Wheelbase	33" (83.8 cm)	41.5" (105.4 cm)	41.5" (105.4 cm)	65" (165.1 cm)	65" (165.1 cm)	45" (114.3 cm)	45" (114.3 cm)
	Dry Weight	215 lb (98 kg)	278 lb (126 kg)	289 lb (131 kg)	572 lb (260 kg)	532 lb (241 kg)	420 lb (191 kg)	420 lb (191 kg)
	Overall Vehicle Size (L x W x H)	48 x 31.5 x 28" (121.9 x 80 x 71.1 cm)	61.3 x 36.8 x 38.5" (155.6 x 93.3 x 97.8 cm)	61.8 x 36.8 x 38.5" (156.8 x 93.3 x 97.8 cm)	85 x 48 x 58" (215.9 x 121.9 x 147.3 cm)	85 x 48 x 55" (215.9 x 121.9 x 139.7 cm)	65 x 42 x 42" (165.1 x 106.7 x 106.7 cm)	65 x 42 x 42" (165.1 x 106.7 x 106.7 cm)
	Ground Clearance	4" (10.2 cm)	4" (10.2 cm)	4" (10.2 cm)	9" (22.9 cm)	6" (15.2 cm)	5.7" (14.5 cm)	5.7" (14.5 cm)
	Seat Height	23" (58.4 cm)	27" (68.6 cm)	27" (68.6 cm)	N.A.	N.A.	32" (81.3 cm)	32" (81.3 cm)
	Fuel Capacity	1.2 gal (4.5 L)	1.6 gal (5.9 L)	2.0 gal (7.8 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)
	Rear Box Dimensions (L x W x H)	N.A.	N.A.	N.A.	17 x 32 x 3" (43.2 x 81.3 x 7.6 cm)	N.A.	N.A.	N.A.
	Front/Rear Rack or Box Capacity	N.A.	N.A.	15 lb / 30 lb (6.8 kg / 13.6 kg)	50 lb (22.7 kg)	N.A.	N.A.	N.A.
	Payload Capacity	N.A.	N.A.	45 lb (20.4 kg)	50 lb (22.7 kg)	N.A.	N.A.	N.A.
	Colors	Pink Power, Lime Squeeze	Pink Power, Lime Squeeze	Velocity Blue	Indy Red	Cruiser Black / Lime Squeeze or Bright White / Indy Red	Avalanche Gray	Indy Red

POLARIS®

OFF-ROAD VEHICLES

POLARIS.COM/OFFROAD

POLARIS
GENERAL

POLARIS
RANGER

POLARIS
RZR

POLARIS
SPORTSMAN

POLARIS
ACE

WARNING: The Polaris off-road vehicles can be hazardous to operate and is not intended for on-road use. Driver must be at least 16 years old with a valid driver's license to operate. Passengers must be at least 12 years old. Drivers and passengers should always wear helmets, eye protection, and seat belts. Always use cab nets or doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All drivers should take a safety training course. Call 800-342-3764 for additional information. Check local laws before riding on trails. All claims based on IHS Automotive. Polk total full-size new U.S. Automatic ATV registrations between October 2015 and December 2016. HIGH LIFTER and HIGH LIFTER OUTLAW are trademarks of HIGH LIFTER PRODUCTS, INC. Bluetooth® is a registered trademark of Bluetooth Sig. Inc. All rights reserved. ©2017 Polaris Industries Inc. all pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice.

Youth models have special age restrictions: the Polaris RZR® 170 and ACE 150 are intended for operators age 10 and older, 50-cc ATV models are intended for operators ages 6 and over, 110-cc ATV models are intended for operators ages 10 and older, and the 200-cc ATV is intended for operators age 14 and older. All Polaris youth vehicles require adult supervision at all times for operators under age 16.